

**Centurion Cold Weather Frost Cape with Ear Defender compatibility:  
Suitable for use with all Centurion helmets.**

**GB****Centurion Frost Cape with Ear Defender****Compatibility - to fit to all helmets including Centurion Reflex helmet:**

Firstly, separate the top of the liner from the bottom/sides section and while holding the bottom section, ensuring that the Centurion logo is facing outwards and at the back of the helmet, insert the bottom section into the helmet, between the back 2 cradle straps and shell at the rear of the helmet. With the bottom section under the 3 cradle straps, position the bottom/sides section so that it sits around the outside of the headband. Then attach the front part of the top and bottom of the liner using the velcro, ensuring that the sections are fed through and attached between the headband and the helmet peak (sweatband on inside). Finally, attach the four velcro tabs that are on each side of the central cradle strap (two each side of the helmet), so that the top and bottom parts of the liner are attached together. The liner can be tucked behind the 4 headband retainer tabs for neatness, whilst allowing the headband to be adjusted.

**An alternative method of fitting the Cape with fitted Fleece Liner to helmets (excluding Reflex):**

Firstly remove the Cradle Headband Assembly. To do this, carefully push the 6 white kit brackets (held at the end of the webbing) out of the helmet shell. Then feed the kit brackets carefully through the six holes in the top of the Fleece Liner. Ensure that the two kit brackets at the front of the headband go through the two holes at the front of the Fleece Liner (where there is no zip) and that the two kit brackets at the rear (by the headband strap) go through the two rear holes of the Fleece Liner (the deepest part of the Fleece Liner). Once the 6 kit brackets have been inserted through the 6 holes in the Fleece Liner, the whole assembly needs to be reinserted into the helmet shell. Position the kit brackets above the correct holes in the helmet shell and then carefully push the kit brackets into the holes until firmly in place.

The Cape allows for the fitting of helmet mounted ear defenders. Simply reposition the two side mesh flaps so that they are held down by the velcro at the bottom of the Cape. Then the ear defenders can be pushed through the holes - ensure that the Cape material is clear from the ear defenders so that it does not affect the seal around the ear and therefore the attenuation performance of the ear defenders.

In addition to the above a Face Warmer (S50FW) is available to fit onto the Frost Cape via velcro located each side of the Frost Cape at the front. The Face Warmer can also be positioned around the rear of the Frost Cape when not required.

EC Type-Examination by: BSI Product Services, Maylands Avenue, Hemel Hempstead, Herts. HP2 4SQ, UK (Notified Body No. 0086)