

# Technical Data Sheet

**CENTURION**

**CENTURION**  
**RAPTOR Kestrel**  
 Safety Eyewear Range

Quality, comfortable spectacles with adjustable temple length for personal fit. Lens with Anti-Scratch and Anti-Fog coating. Available in Clear and Smoke.



Kestrel Spectacles

Specification

Lens Colour:	Clear, Smoke
Lens Coatings:	Anti-Scratch and Anti-Fog
Lens thickness:	2.2mm
Lens Base curve:	9
Nose bridge:	Moulded
Weight:	25g
Adjustment:	Temple length adjustment
Accessories:	Storage and cleaning soft pouch with pull cord and adjustable neck hangcord
Suitable Applications:	General industry, Construction, Medical and Laboratory
Pack quantity:	10 per inner box (can be used for point of sale display purposes)
Packaging:	Box size 19 x 28 x 29.5cm, box weight 0.37kg
Code:	Clear - S70KESTREL-CASAF, Smoke - S70KESTREL-SASAF

Materials

Frame:	Charcoal Grey Polycarbonate
Lens:	Clear or Smoke Polycarbonate



Standards

European Standard:	EN 166 : 2001
Lens Markings:	Clear - 2C-1,2 CSP 1 F , Smoke - 5-2,5 CSP 1 F
Frame Markings:	CSP CE EN 166 F
	2C-1,2: Filter code UV light. Good colour perception. 1: Optical Class 1 - best class for continuous work. F: Low energy impact 45m/s. 5-2,5: Protection against sunglare for industrial use. Smoke Grey.

Storage / Lifetime

Store eyewear in a dry area at room temperature and sheltered from sunlight. Eyewear should be transported and kept in the original packing.

Under normal circumstances; eyewear should provide adequate protection for up to 6 months. Scratched lenses should be replaced or disposed.

Cleaning

Lenses are to be cleaned regularly. Never clean when dry; always use water at room temperature (20°C ± 5°C) with mild detergent. Disinfectant in line with manufacturers instruction can be added to the cleaning solution to disinfect lenses.