



Technical Data Sheet

Concept™ Roofer

Light, strong and comfortable helmet with Premium wheel Ratchet headband ensuring secure fit.



Specification	<p>Colours: White (W), Green (G), Blue (B), Orange (O), Yellow (Y), Red (R), Black (K) High Visibility Yellow (HVY) and High Visibility Orange (HVO)</p> <p>Peak: Full (40mm) or Reduced (20mm)</p> <p>Size: 52-63cm</p> <p>Options: Full or Reduced Peak, Chinstrap (S30E), Retractable Eye Shield (S579)</p> <p>Accessories: Compatible with  range of face and hearing accessories</p> <p>Weight: Full 340g, Reduced 330g</p> <p>Corporate Badging: Front: 85 x 50mm or 25 x 60mm, Sides: 80 x 35mm, Back: 100 x 20mm</p> <p>Unique Features: Ventilation (crown and rear), VentPlugs, 'Push and Turn' Premium Ratchet headband, Internal card holder for identification or medical information (credit card size 54 x 85mm)</p> <p>Helmet Accessories Clip: Use  accessories clips (S570) supplied with Carriers and Ear Defenders</p> <p>Packaging: 10 per colour, box size 47 x 30.5 x 56cm, Full Peak box weight 4.24kg Reduced Peak box weight 4.2kg</p> <p>Code: S08*RJ (Reduced Peak) S09*RJ (Full Peak) *Insert Colour code of helmet (ie. W for White)</p>				
Materials	<p>Shell: ABS (Acrylonitrile-Butadiene-Styrene)</p> <p>Cradle: 6 Point Terylene webbing</p> <p>Headband: LDPE (Low Density Polyethylene)</p> <p>Sweatband: Hydro-Flock</p> <p>Ratchet: Polypropylene, black foam 6mm</p>				
Standard & Options	<p>European Standard - EN 397:1995, EN 50365 - Electrically insulating helmets for use on low voltage installations</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">Options within EN 397:</td> <td>LD (Lateral Deformation) -30°C (Low Temperature Performance)</td> </tr> <tr> <td>Options in addition to EN 397:</td> <td>-40°C (Low Temperature Performance)</td> </tr> </table>	Options within EN 397:	LD (Lateral Deformation) -30°C (Low Temperature Performance)	Options in addition to EN 397:	-40°C (Low Temperature Performance)
Options within EN 397:	LD (Lateral Deformation) -30°C (Low Temperature Performance)				
Options in addition to EN 397:	-40°C (Low Temperature Performance)				
Storage / Lifetime	<p><u>Storage:</u></p> <ul style="list-style-type: none"> - Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C) - May be stored in the dark for up to 5 years - Do not store in direct/high heat or sunlight as this may distort the shell <p><u>Lifetime:</u></p> <ul style="list-style-type: none"> - The Centurion helmet has an in-use life to up to 5 years - Excessive wear and tear can considerably reduce the lifespan of the product 				
Cleaning	<ul style="list-style-type: none"> - Clean using warm soapy water and soft cloth - Do not use solvents or abrasives 				

